



Water distiller ADE-40

Purpose: The device is designed for production of distilled water by heating of raw water to boiling with subsequent condensation of the generated steam resulting in the distillate with a temperature from +40°C to +85°C.

The electrical conductivity of distilled water: < 3,0 μS/cm

Design features:

- A body and main parts are made of high-alloy stainless steel AISI 321 / 304.
- Type of heating elements– tubular electric heaters.
- Tubular condenser.
- Separate water supply circuits allow separate water feeding for evaporation and cooling.
- Demountable design of the condensation chamber for visual monitoring of scale formation, easy sediment cleaning, easy maintenance and repair.
- Automatic control of the water level in the evaporation chamber.
- Steam is cleaned from raw water droplets by a special unit.
- A distiller can be combined with a purified water tank into an automatically operating single system.
- A removable cooler* allows distillate cooling.
- Lifetime: at least 8 years, warranty period: 14 months, MTBF (Mean time between failures): at least 3,500 hours



Safety system:

- Automatic maintenance of water amount used for evaporation.
- Automatic shutdown of the tubular electric heater if the water level in the evaporation chamber drops below the allowable level.
- Automatic shutdown of the distiller (tubular electric heaters) when the water storage tank is full.

Characteristics of electric water distiller ADE-40

Parameters	ADE-40
Productivity, liters per 1 hour	40 (-10%)
Voltage	380 V (50 Hz)
Power consumption, KW	27,0
Consumption of raw water, liters per 1 hour	320 (±10%)
Overall dimensions (L×W×H), mm	700×500×800
Weight, kg	40

* - the item is not included in a standard set. Sold separately.